

## VARISPIN 4A MULTI CENTRIFUGE

Compact centrifuge specific for frequent application

### Main Features >>>

#### ■ Compact design with maximum use of a space

- No space limit in laboratory due to very small footprint.
- Superior profile to have 8 pieces of 15ml tube in spite of small size.

#### ■ High visibility of controller

- Blue LCD screen for process monitoring and easy touch pad for operation.

#### ■ Specific tube size

- 10ml & 15ml size of tubes are available.



### Standard Specifications >>>



Max. RPM	4,000 RPM
Max. RCF	2,075 xg
Max. Capacity	15ml x 8
Noise Level	≤60dB
Set Time	99 min 59sec or continuous
Time Count	From start / From set-up RPM
Program	10 memory
Display	Blue LCD
RPM Range	400 to 4,000 RPM
Display Message on screen	RPM(RCF), Time, Program
Power Supply	220V / 50~60Hz
Power Consumption	150W
Dimension(W x D x H)	291 x 415.5 x 228mm
Weight (without rotor)	14kg











保吉生化學股份有限公司  
BIO-CHECK LABORATORIES LTD.

台北 | (02) 2246-7799  
台中 | (04) 2371-9412  
台南 | (06) 238-9287  
高雄 | (07) 222-9968

Order Information >>>

ITEM	DESCRIPTIONS	ORDER CODE
VARISPIN 4A Set	VARISPIN 4A, with rotor AL815D, including 15ml stainless steel sleeves, 220V/50 -60Hz	V4A - SET
VARISPIN 4A	VARISPIN 4A, without rotor, 220V/50 -60Hz	V4A - MB
AL815D	15ml x 8 fixed angle rotor with 15ml stainless steel sleeves	V4A - AR1

Available rotors >>>

AL815D	F15A-3	F15A-5				
 <p>Fixed Angle Rotor <math>\angle 40^\circ</math> 8 x 15ml Radius(mm) : 116</p>						
						
Volume (ml)	3	5	10	15	15 Conical	
Number per rack / rotor	8	8	8	8	8	
Adapter bore (mm)	13.5	13.5	18.0	18.0	18.0	
Max. height for use (mm)	120	142	131	131	131	
RPM	4,000	4,000	4,000	4,000	4,000	
Radius (mm)	97.4	111.2	111.6	116.0	110.2	
RCF	1,742	1,989	1,996	2,075	1,971	



保吉生化學股份有限公司  
BIO-CHECK LABORATORIES LTD.

台北 | (02) 2246-7799  
台中 | (04) 2371-9412  
台南 | (06) 238-9287  
高雄 | (07) 222-9968